

WHAT IS CLAIMED IS:

1. A detecting device comprising:

a transmission line:

an optical pickup which connecting the

5 transmission line and having a photo-detecting element,
the optical pickup receives a first reference potential
from a transmission line, sets the potential to a
second reference potential affected by a noise
component in the transmission line, generates a
10 detection signal from the photo-detecting element on
the basis of the second reference potential, and
outputs the detection signal and the second reference
potential through the transmission line; and

a differential amplifier which receives the
15 detection signal and the second reference potential
from the optical pickup through the transmission line,
and outputs potential difference between the detection
signal and the second reference potential.

2. A detecting device according to claim 1,
20 wherein the differential amplifier is operated on the
basis of a third reference potential having the same
potential as that of the first reference potential.

3. A detecting device according to claim 1,
wherein the differential amplifier is operated on the
25 basis of a third reference potential connected to the
first reference potential.

4. A detecting device according to claim 1,

wherein the differential amplifier has a main portion which generates the first reference potential.

5. A detecting method comprising:

supplying a first reference potential through a
5 transmission line;

setting the potential to a second reference
potential affected by a noise component in the
transmission line;

generating a detection signal from a photo-
10 detecting element on the basis of the second reference
potential;

outputting the detection signal and the second
reference potential through the transmission line;

receiving the detection signal and the second
15 reference potential from the optical pickup through the
transmission line; and

outputting potential difference between the
detection signal and the second reference potential
with a differential amplifier.

20 6. A detecting method according to claim 5,
wherein the differential amplifier is operated on the
basis of a third reference potential having the same
potential as that of the first reference potential.

25 7. A detecting method according to claim 5,
wherein the differential amplifier is operated on the
basis of a third reference potential connected to the
first reference potential.

8. A detecting method according to claim 5,
wherein the differential amplifier has a main portion
which generates the first reference potential.

9. An optical disk device comprising:

5 a transmission line:

an optical pickup which connecting the
transmission line and having a photo-detecting element,
the optical pickup receives a first reference potential
from a transmission line, sets the potential to a
10 second reference potential affected by a noise
component in the transmission line, radiates an optical
disk with a laser beam to receive the reflected light
by a photo-detecting element, generates a detection
signal from the photo-detecting element on the basis of
15 the second reference potential, and outputs the
detection signal and the second reference potential
through the transmission line;

a differential amplifier which receives the
detection signal and the second reference potential
20 from the optical pickup through the transmission line,
and outputs potential difference between the detection
signal and the second reference potential;

a focusing control circuit which generates a
focusing control signal for moving an objective lens,
25 which condenses the laser beam on the optical disk, in
a direction of an optical axis on the basis of an
output from the differential amplifier; and

a tracking control circuit which generates a track driving signal for moving the objective lens in a direction crossed at right angles with the optical axis on the basis of the output from the differential amplifier.

5

10. An optical disk device according to claim 9, wherein the differential amplifier is operated on the basis of a third reference potential having the same potential as that of the first reference potential.

10

11. An optical disk device according to claim 9, wherein the differential amplifier is operated on the basis of a third reference potential connected to the first reference potential.

15

12. An optical disk device according to claim 9, wherein the differential amplifier has a main portion which generates the first reference potential.